# McCloskey

# **High Performance Cone Crusher**

The McCloskey<sup>™</sup> C2 Cone Crusher is the ideal portable secondary crushing solution for the operator requiring performance rates up to 300TPH. It is designed for optimum versatility in crushing spreads, with easy conversion from the finest to the coarsest cavity, adjustable speed to produce a higher percentage of on-spec product, and fewer crushing stages, lowering cost and saving energy. Both the C2 & C2R have full-level features such as load and material level monitoring, full hydraulic push button Closed Side Setting (CSS) adjust and a full hydraulic relief system.

# **F**eatures

- MC200 Cone
- Tracked
- Integrated hopper with folding rear door

A STATISTICS AND A STAT

H2

- I-beam plate fabricated chassis construction
- Large gap between crusher discharge and main conveyor
- Fast setup time

- Open chassis design for ease of maintenance
- High speed, high throw 200Hp cone



#### Feeder

Heavy Duty steel hopper with adjustable feed rate via control panel, remote control or fully automatic regulation with feedback from the cone

#### **Crushing Chamber**

Built to be reliable in the toughest operating conditions, the cone on the C2 has a minimum setting of 13mm (0.5") and a maximum feed opening of 185mm (7.25")

#### Material Flow

Large clearance between crusher discharge and the main conveyor feedboot prevents bottlenecking.

### mccloskeyinternational.com

Long Stroke (77mm)

Excellent productivity through long stroke and high speed in terms of capacity, reduction and end product shape.

## **SPECIFICATION DATA**

## **Dimensions and Capacities**

Engine	360 Hp (268 kW)
Cone	MC200
Feed Opening	38" (914mm)
Feeder Belt Width	42" (1050mm)
Hopper Volume	5m³ (6.5yd³)
Crusher Drive	Direct Drive
CSS Adjustment	Hydraulic
Transport Height	11' - 1.8" (3.4m)
Transport Length	54' - 4.7" (16.6m)
Transport Width	9' - 1.4" (2.8m)
Weight	106,770 lb (40,470kg) (est.)
Stockpile Height Main Conveyor	14' - 0.5" (4281mm)
Main Conveyor Belt Width	48" (1200mm)

©Copyright 2020 McCloskey International. All rights reserved. McCloskey is a trademark of McCloskey International.

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate — McCloskey International assumes no liability resulting from errors or omissions in this document.